



MD-01N and MD-02N

One block and Two block Dry Baths with interchangeable heating block modules for a variety of applications. Models include PI controller for easy temperature selection, rapid heat up and excellent stability. Temperature may be set in 0.1°C increments from above ambient to 150°C. Temperature uniformity  $\pm 0.2^\circ\text{C}$ , temperature accuracy  $\pm 0.2^\circ\text{C}$ . Includes temperature calibrated function. RS-232 output for datalogger. Includes a temperature calibration function and a timer 0 to 9999 minutes. Temperature range: Ambient plus 5°C to +155°C at an accuracy of  $\pm 0.2^\circ\text{C}$   
 Ext Dims: 260Lx210Wx80D mm  
 Block dims: 105Lx80Wx50mmD with handy lift out device.

Block Models	Tube Capacity / Dia	No. of Wells	Depth of Wells
AB-15	15ml / 17mm	12	40mm
AB-10	10ml / 16mm	12	
AB-2.0	2.0ml	20	35mm
AB-1.5	1.5ml	20	34mm parallel
AB-0.5	0.5ml	20	28mm tapered
AB-0.2	0.2ml	30	16mm tapered
AB-MP	96 Well Microtitre Plate (2 blocks)		

*Custom blocks available on request.*