

Plasma Storage Freezers (-35°C)

AUSTRALIAN MADE




TPSFU-970-40-600


UPRIGHT STYLE OPERATING TEMPERATURE -35°C (-40°C TPSFU-970-600)



TPSFU-350-35-160



TPSFU-594-35-450



TPSFU-970-40-600

FEATURES

Our Plasma Storage Freezers have been designed specifically for the storage of Plasma and Blood Products, below -35°C. Thermoline Plasma Freezers are supplied standard with our Thermoscan TS-2000 Alarm System which has been adapted in our Blood Storage Refrigerators designed and built to Australian Standard AS3864. Our Smaller 80Lt freezers (see page F5) is an ideal unit for the smaller regional facilities or situations that require a smaller system in the heavy peak periods.

- Designed and Manufactured by Thermoline Scientific in 3 versatile capacities 350Lt to 970Lt
- Manufactured to meet the Australian Standard AS3864-1997
- Single stage refrigeration system using Ozone friendly refrigerants
- Easy set up, plug in power, activate alarm system when conditions reached its that easy
- Static stainless steel plate shelving, storage of plasma bags conveniently packed flat
- Circular 7 day chart recorder fitted as standard
- Full alarm system for Hi/Lo temperatures, power loss, unique test feature all battery backed
- Polished Stainless Steel internal liner
- Fully insulated construction for efficient and cheaper running cost
- Manual Defrost feature allows you to control when defrosting is carried out.
- TCPF-80-40 Chest style having 80Lt capacity making ideal for those smaller facilities or a convenient back up system

Safety Features

- ✓ Thermoscan TS-2000 alarm system
- ✓ Over Current protection
- ✓ Refrigeration overload protection

Optional Features

TPD-1, Automatic phone dialer to call when alarms are activated (even your mobile phone)

*POWER GUARD, offering protection against Low Voltage, High Voltage Spikes *NEW PRODUCT**

ORDER CODE	DIM. INT HxWxD cm	BAG CAPACITY	LITRES CAPACITY	DIM. EXT HxWxD cm	SHELVES	ELECTRICAL 240V 50Hz	APPROX WEIGHT Kg
TPSFU-350-35-160	111x 55x58	160	350	173x71x 78	4	5A	130
TPSFU-594-35-450	127x79x62	450	594	198x107x91	4	8A	150
TPSFU-970-40-600 (-40°C)	144x95x71	600	970	219x115x95	5	12A	260