



LEB

- 4, 6, & 8 Extraction Places
- Bath construction of high grade Stainless Steel
- Digital PID control insures accuracy
- Wide temperature range
- Adjustable Compensation insures product is at set temperatures
- Timer functions for delay start time, & duration time
- Touch pad provides easy setup of conditions

Safety Devices

- √ Over temperature protection
- √ Over current circuit protection
- √ Alarm function for controller error
- √ End of cycle indication
- √ Lock mode for experimental application (input to Jog-Shuttle can be disabled)

Model	LEB-104D	LEB-106D	LEB-108D
Int Dims (wxdxh mm)	620x160x130	920x160x130	920x320x130
Ext Dims (wxdxh mm)	682x310x320	982x310x320	982x470x320
No. of extraction Holes	4	6	8
Top opening dia. (mm)	110 dia	110 dia	110 dia
Capacity	8 litre	12 litre	22 litre
Heater	2kW	3kW	3kW
Temp Range	Ambient +5°C to 99°C		
Temp Accuracy	±0.2°C		
Temp Uniformity	±1°C		
Display	4 Digit LED Display		
Controller	Digital PID Controller		
Timer	99hr 59min)		
Material Stand	Stainless Steel		
Material External	Powder Coated Steel		
Safety	Over Temp Protector		
Power Supply	220VAC, 50 Hz		