

ECONOMY PHARMACY REFRIGERATORS

(+5°C)

Image: TEPR-145-1-GD, TEPR-440-1GD and TEPR-740-2-GD



Economy Pharmacy Refrigerators

- Internal Forced Air Flow
- Digital Temperature Display with High and Low Temperature Alarms
- Max/Min Temperature Logging
- Internal Light
- Cable/Monitoring Port Hole
- Door Key Lock
- Frost Free Operation
- Adjustable/Removable Shelves

QCPP APPROVED

The Quality Care Pharmacy Program (QCPP) is a quality assurance program aimed at raising the standards of service that pharmacies provide to the public. The program is based on business and professional standards developed by the Pharmacy Guild and other industry stakeholders.

Head Office Phone (02) 9604 3911
Head Office Fax (02) 9725 1706

Email info@thermoline.com.au
Web www.thermoline.com.au

 **Thermoline**
S C I E N T I F I C
H I G H E R S T A N D A R D S I N S C I E N C E

PRODUCT DETAILS

Thermoline has specially developed pharmacy and vaccine refrigerators, suitable for retail pharmacies, medical centres, universities and veterinary hospitals where pharmacy and/or vaccine products are required to be stored safely. Four larger premium models are also available up to 1150 litres in capacity for increased storage requirements.

Temperature is precisely controlled electronically at +5°C in ambients up to 32°C. The digital display incorporates high (+8°C) and low (+2°C) temperature alarms, which emit visual and audible signals to notify the operator when an alarm has been activated. Connection to a building management system (BMS) is available as an optional extra.

A low temperature, protective, cut-out (LTPC) can be fitted on request to prevent products inside the refrigerator from freezing (particularly important for the storage of vaccines). This independent device will turn off the refrigeration system should the control fail in the cooling mode.

The models TEPR-145 and TEPR-200 have a grey metal exterior, and white colorbond interior. Larger models TEPR-440 and TEPR-740 have a grey metal exterior and interior complete with stainless steel floor and white Colorbond walls. Insulation is high efficiency injected polyurethane foam. All models are standard with glass self closing lockable doors. Glass doors enable the product to be viewed without loss of conditions inside the refrigerator.

Optional Accessories
POWER GUARD - Offers protection against low voltage, high voltage spikes and limited lightning.
External connection for BMS (in-house building management system)
Additional shelving
TPD-1 : Phone dialler. Analogue line only.
LTPC : Low temperature protective cut out

SPECIFICATIONS

Model	Internal Dimensions (HxWxD mm)	Capacity (litres)	External Dimensions (HxWxD mm)	Shelves	Electrical	Weight (kg)
TEPR-145-1-GD	680x520x430	145	850x600x600	4	0.9A	62
TEPR-200-1-GD	1080x450x430	200	1590x550x590	4	2.5A	70
TEPR-440-1-GD	1300x500x520	440	2000x650x750	4	4.2A	150
TEPR-740-2-GD	1300x850x520	740	2000x1000x750	4	4.2A	240

Thermoline Scientific have been manufacturing and distributing high quality laboratory and scientific testing equipment since 1970. Over this time, Thermoline has grown to be a leading brand in the science industry, with our equipment being used in small and large Hospitals, Universities and Research Laboratories across Australia and the Asia Pacific region.

We're proud to say that we are 100% Australian owned and operated.

Head Office Phone (02) 9604 3911

Head Office Fax (02) 9725 1706

Email info@thermoline.com.au

Web www.thermoline.com.au