

### Features & Benefits

- Ideal for quick spin downs and micro filtration
- Includes two rotors with delivery
- Transparent blue lid
- Dual door interlock design
- Easy to remove rotor is seated on a tapered shaft
- Starts and break in seconds
- Start/Stop functions by closing/opening lid



### Technical Specifications:

Maximum Speed	7,000rpm
Maximum RCF	2,680 x G
Run Time	Continuous
Driving Motor	DC Motor
Power	240V/60Hz
Noise Level	≤ 45 dB
Dimensions (WxDxH)	150 x 150 x 117mm
Weight	0.5kg

### Ordering Information:

Product Code	Description	Pack Size
400.003.005	Centrifuge supplied with 400.003.010 & 400.003.011 Rotors	Each

### Accessories



400.003.010 Rotor  
(Micro tubes not supplied)



400.003.011 Rotor  
(PCR tubes not supplied)



### Technical Information:

Rotor Product Code	400.003.010	400.003.011
Maximum Speed	7,000rpm	
Maximum RCF	2,680 x G	
Capacity	1.5mL / 2mL x 8 0.2mL* x 8 0.5mL* x 8	0.2mL PCR Tube x 16 0.2mL PCR Tube Strip of 8 x 2
Material	High Strength Plastic	

\*Adaptors required

### Ordering Information:

Product Code	Description	Pack Size
400.003.010	Rotor Plastic for 0.2/0.5/1.5/2mL x 8 (adaptor required for 0.2/0.5mL)	Each
400.003.011	Rotor Plastic for PCR Strip x 2	Each
400.003.015	Adapter for 2mL to 0.2mL tube	PK24
400.003.016	Adapter for 2mL to 0.5mL tube	PK24

